

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交寄本文档的内容。侵犯者将承担赔偿责任。 本公司保留对涉及发明、实用新型和外观设计的所有权利。

FOR-1754 Rev.1.2

2



3


4

5

6

Dimensional tolerance(mm)					Length tolerance(mm)				
0	>30	>60	>100	>150	0	5000	10000	>30000	
30	60	100	150		5000	10000	30000		
±0.25	±0.35	±0.55	±0.80	±1.10	±55	±105	±205	±505	
额定电压/Current /Rated Voltage/Current						1000V/50A			
绝缘电阻/Insulation resistance						≥100MΩ			
插拔次数/Mechanical working life(mating cycles)						100			
耐电压/Withstanding voltage						4250V DC			
使用温度范围/Operating temperature(°C)						-40~-+125°C			
防水等级/Levels of protection						IP67			
接线方式/Terminal						Crimp Termination			
线径范围/Wire range(AWG/mm)						10AWG/6mm ²			
剥线长度/Stripping length(mm)						8~9			
符合RoHS环保要求/Conform to RoHS						Yes			



MATERIAL: /		SURFACE: /			
MAT NO.:		 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD			
STATUS: /					
APPD:		NAME: ESS-50A-06-C-OR-00			
CHKD:					
DRFT: Luo XF 2022.12.06		DRAWING NO.: /		REV	00
	SIZE: A4		TYPE: CUSTOMER DRAWING	SCALE: 1:1	SHEET 1/1

1

2

3

4

5

6

REV	ECN	DESCRIPTION	DRFT	DATE