



公差/General tolerances(mm)	0	~3	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.45	±0.57	±0.70	±0.85	±1.05	±1.25	±1.50	±1.75	±2.00	±2.50	±2

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)	600/52	600/52	600/5
IEC 标准/IEC Standard:	III/3	III/2	II/2
过压类别/Oversvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage/Current(A)	600/57	/	/
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	6	/	/
螺丝扭矩/Torque Tightening(N·m/Lb·in)	M4: 1.2/10.53	/	/
线缆范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	20-6 / 0.5-10	/	/
剥线长度/Stripping length(mm)	10-12	/	/
使用温度范围/Operating temperature(°C)	-40-+105	/	/
符合RoHS环保要求/Conform to RoHS	Yes	/	/

ITEM	NAME OF PART	MATERIAL	NOTES
6	Spring	Stainless steel	/
5	Clamp	Copper	Ag Plated
4	Cage	Copper alloy	Ni Plated
3	Screws	Copper alloy	MANI Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0



APFD: 兰春华	2024.11.27	NAME	MATERIAL:	SURFACE/COLOR:
CMDD: 刘强	2024.11.27	DRAWING NO.	MAT NO./REV: 10010002922-1 / 00	MAT STATUS: 批量
DRFT: 杨树杰	2024.11.26	TYPE	SEDGK-10.16-02P-1Y-200AAZ (H)	
M4	(inch)	CUSTOMER DRAWING	DRAWING STATUS	SCALE
		200321137	已发布	1.5:1
			SHEET	1/1

REV	00	ECN	DESCRIPTION	DRFT	DATE
				杨树杰	2024.11.26

1 2 3 4 5 6