

## Overview

### Product information



## Relay base-DSRT05A-3-00A(H)-30020000057

DSRTrelay base,used for1PDTrelay,screw connection

### Product advantages

- ☑ Plug-in relay socket
- ☑ Safe isolation between coil and contacts
- ☑ 16A, 1PDTgrade

### Product certification

## Technical data

### Product drawing

### 3D model

□

### Environmental data

Ambient temperature (storage/transport)

-40 °C ... +85 °C

Ambient temperature (operation)

-20 °C ... 50 °C

### Technical data

Rated voltage UN

300V

Installation location

Arbitrary

Assembly instructions

DIN35 rail

### Connection data 1

Connection name

enter

Connection method

Screw connection

Stripping length

7-8mm

screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm <sup>2</sup>
Connectable guide cross section AWG	20-14AWG

#### Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm <sup>2</sup>
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

#### Dimension

length	73.3mm
width	16mm
Depth including bracket	29.5mm

#### Accessories

#### Business data

Order number	30020000057
Packing unit	20 SKT
Minimum order quantity	20 SKT
Products weight (without packaging)	27g