

## Overview

### Product information



**Relay base-DPKF08A-E3-00A(H)-30020000049**

DPKFrelay base,used for2PDTrelay,screw connection

### Product advantages

- ☑ Plug-in relay socket
- ☑ Safe isolation between coil and contacts
- ☑ 12A, 2PDTgrade
- ☑ Arc partition between adjacent columns
- ☑ Anti-touch cover at the top of the screw

### Product certification

## Technical data

### Product drawing

### 3D model

□

### Environmental data

Ambient temperature (storage/transport)	-40 °C ... +85 °C
Ambient temperature (operation)	-20 °C ... 50 °C

### Technical data

Rated voltage UN	300V
Installation location	Arbitrary
Assembly instructions	DIN35 rail

### Connection data 1

Connection name	enter
Connection method	Screw connection

Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm <sup>2</sup>
Connectable guide cross section AWG	20-14AWG

#### Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm <sup>2</sup>
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

#### Dimension

length	69.6mm
width	25mm
Depth including bracket	29.2mm

#### Accessories

#### Business data

Order number	30020000049
Packing unit	20 SKT
Minimum order quantity	20 SKT
Products weight (without packaging)	62g