

## Overview

#### Product information



# ESS-120A-25-S-OR-00-20160000031

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: Screw, Contact type: Needle

### Product advantages

- ☑ Exclusive patents
- ☑ IP67 protection
- ☑ With safety locking latch
- ☑ The plug can rotate 360° after assembled
- ☑ The socket is with hand-proof protection
- $\ensuremath{\mbox{\sc W}}$  With color-coded and mechnism-coded desgin avoiding misplug

#### Product certification





### Technical data

Drod		dra	· ina
Prod	uci	ura	wing

3D model

# Wiring data

Wiring mode	Screw
-------------	-------

#### **Environment condition**

Protection grade (pair plug)	IP67
Ambient temperature (operation)	-40°C ~ +125°C
Ambient temperature (storage/transportation)	-40°C ~ +80°C
Altitude	2000m

## Mechanical properties

Plugging times	100
Insertion force	<60N
Pullout force	>10N
Standards and specifications	
Standard/Specification	UL4128
Material data	
Insulating material	Nylon
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Sealing ring material	Silicone
Contact material	Copper alloy
Shell color	Orange

# Electrical parameters

Flammability rating

Pollution level	3
Rated current	120A
Rated current	UL DC1500V
Insulation resistance	>5000MΩ
Contact resistance	≤0.5mΩ

UL94V-0

Accessories			

Business	data
Dusiliess	uala

Order number	20160000031
Packing unit	32

Minimum order quantity	50
Products weight (without packaging)	22.65