

Overview		
Product information		
	Energy Storage Con cross section: 16 mm	<b>6-B-BK-00-20160003064</b> nector, Product range: ESS socket, Color: black, Wire <sup>2</sup> , Rated voltage: 1500V, Rated current: 100 A, Busbar, Contact type: Needle
Product advantages		
<ul> <li>Exclusive patents</li> <li>IP67 protection</li> <li>With safety locking latch</li> <li>The plug can rotate 360°after asses</li> <li>The socket is with hand-proof prote</li> <li>With color-coded and mechnism-co</li> </ul>	ection	plug
Product certification		
Technical data		
Technical data Product drawing		
Product drawing		
Product drawing 3D model		
Product drawing 3D model		Busbar
Product drawing 3D model • Wiring data		Busbar
Product drawing 3D model Wiring data Wiring mode		Busbar IP67
Product drawing 3D model Wiring data Wiring mode Environment condition		
Product drawing 3D model 3D model Wiring data Wiring mode Environment condition Protection grade (pair plug)	portation)	IP67
Product drawing 3D model 3D model Viring data Wiring mode Environment condition Protection grade (pair plug) Ambient temperature (operation)	portation)	IP67 -40°C ~ +125°C

Plugging times	100
Insertion force	<60N
Pullout force	>10N
Standards and specifications	
Standard/Specification	UL4128
<i>l</i> aterial data	
Insulating material	Nylon
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Sealing ring material	Silicone
Contact material	Copper alloy
Shell color	Black
Flammability rating	UL94V-0
Electrical parameters	
Pollution level	3
Rated current	UL DC1500V
	100A
Insulation resistance	>5000ΜΩ
Contact resistance	≤0.5mΩ

Accessories

Business data	
Order number	20160003064
Packing unit	32

Minimum order quantity	50
Products weight (without packaging)	27