

## Overview

### Product information



## WS6-TW-PE-11030000322

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG: 24 - 10, Width: 8 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

### Product advantages

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Grounding structure, protection circuit;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Overview

|                                           |                        |
|-------------------------------------------|------------------------|
| Connection method                         | spring-cage connection |
| Number of rows                            | 1                      |
| number of connections                     | 3                      |
| Open-end side panels                      | Yes                    |
| Insulation Materials                      | PA                     |
| Flame retardant grade, in line with UL 94 | V0                     |
| Insulating material group                 | I                      |

|               |              |
|---------------|--------------|
| standard test | IEC60947-7-2 |
|---------------|--------------|

#### Dimension

|                  |        |
|------------------|--------|
| width            | 8mm    |
| End plate width  | 2.5mm  |
| Height           | 39.5mm |
| NS 35/7,5 Height | 40mm   |
| NS 35/15 Height  | 47.5mm |
| length           | 92mm   |

#### Wiring data

|                                           |                        |
|-------------------------------------------|------------------------|
| Strip length                              | 12~13mm                |
| Conductor cross section solid AWG         | 24~10                  |
| Conductor cross section solid             | 0.2~6mm <sup>2</sup>   |
| Conductor cross section flexible          | 0.2~6mm <sup>2</sup>   |
| 2 flexible conductors with a TWIN ferrule | 0.5-2.5mm <sup>2</sup> |

#### IEC Electrical parameters

|                         |   |
|-------------------------|---|
| Rated voltage (III / 3) | / |
| Rated current (III / 3) | / |

#### IEC Electrical parameters

|                     |     |
|---------------------|-----|
| Rated surge voltage | 8KV |
|---------------------|-----|

#### UL Electrical parameters

|               |   |
|---------------|---|
| Rated voltage | / |
| Rated current | / |

#### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

|                                           |            |
|-------------------------------------------|------------|
| Ambient temperature (storage / transport) | -25°C~60°C |
|-------------------------------------------|------------|

#### Mechanical performance test

|                      |                 |
|----------------------|-----------------|
| Mechanical strength  | Passed the test |
| Fixing support       | Passed the test |
| Rotational Pull Test | Passed the test |

#### Electrical performance test

|                       |        |
|-----------------------|--------|
| Voltage drop          | ≤3.2mV |
| Temperature rise test | ≤45 K  |

#### Safety test

|                   |                 |
|-------------------|-----------------|
| Anti-finger touch | Passed the test |
|-------------------|-----------------|

#### Environmental protection

|            |                                 |
|------------|---------------------------------|
| RoHS       | No excessive harmful substances |
| REACH SVHC | Lead 7439-92-1                  |

### Accessories

#### Marker

|                |                        |
|----------------|------------------------|
| Top marker     | ZB8 / WB5              |
| Side marker    | DEK6                   |
| Marker support | DTH5-25×5 / DTH5-25×12 |
| Warning cover  | EEA6                   |

#### Accessories

|                                                    |         |
|----------------------------------------------------|---------|
| Slotted screwdriver size (Blade thickness x Width) | 0.8×5.5 |
| Adjacent jumper (2P)                               | /       |
| Alternate jumper (2P)                              | /       |
| Staggered jumper (2P)                              | /       |

|           |          |
|-----------|----------|
| End cover | D-WS6-TW |
|-----------|----------|

#### Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

#### Marking & Installation

|               |       |
|---------------|-------|
| Marking strip | ZB8   |
| Marker cards  | DBE-1 |

#### Accessories

|           |                      |
|-----------|----------------------|
| End cover | D-WS6-TW             |
| End clamp | E-WS                 |
| DIN rail  | NS35/7.5-1000-00A(H) |

#### Business data

|                                     |             |
|-------------------------------------|-------------|
| Order number                        | 11030000322 |
| Packing unit                        | 20          |
| Minimum order quantity              | 20          |
| Products weight (without packaging) | 26.313      |