

## Overview

## Product information

**SD-M12A-03P-FF-SH8002-20030001064**Sensor/Actuator Female socket,M12,Coding A,Front panel installation/M16\*1.5  
Thread mounted,Soldering cup

## Product advantages

- ✓ Sealing optimization, protection level up to IP68
- ✓ Meet the harsh environment
- ✓ Suitable for various occasions connection technology
- ✓ Compatible with the international and domestic same series products

## Product certification



## Technical data

## Product drawing

## 3D model

□

## Environmental conditions

Ambient temperature	-40℃...105℃
IP class	IP68

## General parameters

Rated current	4A
	250V
Number of potentials	3
Insulation resistance	≥ 100 MΩ
Error-proof coding	A-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

#### Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

#### Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

#### Accessories

##### Accessories

Sealing cap	CAP-M12-MP-8003
-------------	-----------------

#### Business data

Order number	20030001064
Packing unit	/
Minimum order quantity	100
Products weight (without packaging)	/

