

Overview			
Product information			
	Sensor/Actuator Cab	5P-MM-SL8C01-20030000811 ble,PVC,black,UL2517,Male plug,Straight M12,Coding ng cable end,Cable Cable length:1m,UL Certification	
Product advantages	Product advantages		
 ☑ Sealing optimization, protection level ☑ Meet the harsh environment ☑ Suitable for various occasions conn ☑ Compatible with the international and 	ection technology	products	
Product certification			
GRU [®] us ROHS	REACH \$		
Technical data			
Product drawing			
3D model			
Environmental conditions			
Ambient temperature		-25℃85℃	
IP class		IP68	
General parameters			
		4A	
Rated current			
		60V	
Number of potentials		5	
Insulation resistance		≥ 100 MΩ	
Error-proof coding		B-Code	

Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	VO
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications

Cable

Cable type	PVC Black
Cable type(abbreviation)	PVC
UL AWM form	UL2517
Cross section	0.34mm ²
AWG signal wire	22AWG
Wire structure Signal wire	17/0.16mm²
Core diameter (including insulation layer)	1.30±0.05mm
Wire color	1 Brown 2 White 3 Blue 4 Black 5 Gray
Thickness, insulation	0.6mm
Cable outer diameter D	5.4 ±0.2mm

Outer sheath, material	PVC
Conductor insulation material	PVC
Conductor material	Tinned copper
Insulation resistance	≥100MΩ
Conductor resistance	Maximum 59.4Ω/km (at 20 °C))
Nominal cable voltage	300V
Cable test voltage	2000V
Flame retardant	Comply with UL 758/1581 FT1 standard
Halogen free	Yes
mension	
Cable length	1m

Accessories	
Accessories	
Sealing cap	CAP-M12-FP-8001

Business data	
Order number	2003000811
Packing unit	1
Minimum order quantity	100
Products weight (without packaging)	1